


## SERIES CM1

Portable Distribution panels

### Features

- Metal trolleys with supporting frame in plates 20/10 mm with panels to support the components in PVC thickness 10 mm, eyebolts for the lifting and rubberized wheels.
- Covers in unbreakable transparent polycarbonate with spring closure for modular switches.
- Distribution with sockets CEE P17 IP67, equipped with warning lights to indicate the presence of voltage.
- Sockets protected by thermomagnetic-differential circuit breakers.
- Protection degree IP44 to be advanced.
- Instrumentation on request.
- Manufactured according the regulations CEI 17-13/1 EN 60439-1.



| series CM1 | Power-supply                       | Sockets CEE P17                                                                               |                                                                                             |                                                                                               |                                                                                               |                                                                                                 |                                                                                               |                                                                                               |
|------------|------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
|            |                                    | 125A                                                                                          |                                                                                             | 63A                                                                                           |                                                                                               | 32A                                                                                             |                                                                                               |                                                                                               |
| Item       | Through powerlock 3P+N+E 400V 400A | 3P+N+E<br> | 2P+E<br> | 3P+N+E<br> | 2P+E<br> | 3P+N+E<br> | 3P+E<br> | 2P+E<br> |
| CM1400PS   | General thermomagnetic 4P 400A     | 1                                                                                             |                                                                                             | 3                                                                                             |                                                                                               | 1                                                                                               |                                                                                               | 1                                                                                             |
| CM1250PS1  | General thermomagnetic 4P 250A     |                                                                                               |                                                                                             | 2                                                                                             | 1                                                                                             | 2                                                                                               |                                                                                               | 3                                                                                             |
| CM1250PS2  | General thermomagnetic 4P 250A     |                                                                                               |                                                                                             | 3                                                                                             |                                                                                               | 3                                                                                               |                                                                                               |                                                                                               |

**N.B.** Further combinations are possible on request. Other dimensions from the standard ones are subject to the type of set up.