

SERIES FLC

Portable Distribution panels

Features

- Flightcase in naval plywood 10mm, trimmed in aluminium with corners protected by angle bars, panels to support the components in PVC thickness 10mm.
- Swivelling rubberized wheels, reclining recessed lateral handles.
- Opening of the flightcase with two covers, closure through eight lowered clasps.
- Covers in unbreakable transparent polycarbonate with spring closure for modular switches.
- Distribution with sockets CEE P17 IP67, equipped with warning lights to indicate the presence of voltage.
- Sockets protected by thermomagnetic-differential circuit breakers.
- Instrumentation and emergency switch on request.
- Protection degree IP32.
- Manufactured according the regulations CEI 17-13/1 EN 60439-1



Series FLC	Power-supply	Sockets CEE P17						
		63A		32A		16A		
Item	Through powerlock 3P+N+E 400V 400A	3P+N+E 	2P+E 	3P+N+E 	2P+E 	3P+N+E 	3P+E 	2P+E 
FLC400PS1	General thermomagnetic 4P 400A	3		5	1			4
FLC400PS2	General thermomagnetic 4P 400A	9		3				6
FLC250PS	General thermomagnetic 4P 250A	3		3	3			3

N.B. Further combinations are possible on request. SIZES: subject to the type of set up.