

SAFEBOY ULTRA 1

ATEX LED FLOODLIGHT



Features

- Robust LED spotlight, 3 rows
- Plastic housing, impact resistant
- Width, uniform illumination
- Positionable horizontally or vertically
- Protection category IP65
- Voltage: 42V & 24V available
- Optionally available: replacement protection foil for the illuminated surface of the lamp, / tripod with adjustable lighting settings.



Specifications

- Illuminant: 81 x Power LEDs
- Power: 35W
- Luminous flux: ca. 4100 Lumen
- Diffusor: integrated
- Fixing: optional on request
- Cable: 10m H07RN-F (optional 20m. or 30m.)
- Plug: without (ATEX plug on request)
- Weight: 3,2 kg.
- Temperature range: -20°C - +50°C
- Dimensions: 378 x 220 x 140 mm.
- ATEX Identification: II 2 G Ex ib mb IIC T4 Gb / II 2 D Ex ib mb IIIC T130° Db

The explosion-proof LED spotlight Safeboy ULTRA 1 LED combines high light output with high mobility. Thanks to its low weight and extraordinary robustness, it is the ideal lighting solution in demanding and harsh environments. The spotlight is flexible horizontally or vertically openable. Optional accessories such as telescopic stands or magnetic brackets are available

Type - Version	Voltage	Power	Item
Safeboy ULTRA 1 LED 42V	42V AC/DC	35W	290725
Safeboy ULTRA 1 LED 24V	24V AC/DC	35W	290732