

SERIES MODULUS S

Portable Distribution panels

Features

- Low linear density polyethylene enclosure, light and resistant to harsh use and shocks in compliance with Glow wire test 960°C according to EN60695-2-11: 2013, EN60695-2-10: 2013, CEI IEC60695-2-11: 2014, CEI IEC60695-2-10: 2014
- Transparent polycarbonate hinged lid with closing spring to protect the MCBs
- Available with CEE P17 receptacles IP44, IP67 black color and/or Socapex connectors
- Receptacles protected with MCB, RCD and/or RCBO
- LED indicator lights
- Integrated carriage handles
- Stackability
- Custom solutions available on demand
- Built in compliance with CEI EN 61439-1 / CEI EN 61439-2



Series MODULUS	Supply	Protections	CEE P17 Receptacles			
			63A	32A	32A	16A
Articolo			3P+N+E 	3P+N+E 	2P+E 	2P+E 
H3L6312P16N	Cee inlet 400V 63A 3P+N+E IP67 black color	RCBO 4P 63A 30mA (main) and 12 MCBs 1P+N 16A				12
H3L6312P16N1	Cee inlet 400V 63A 3P+N+E IP67 black color	RCD 4P 63A 30mA (main) and 12 MCBs 1P+N 16A				12
H3L636P32N	Cee inlet 400V 63A 3P+N+E IP67 black color	RCD 4P 63A 30mA (main) and 6 MCBs 1P+N 32A			6	
H3L1252PS63N	Cee inlet 400V 125A 3P+N+E IP67 black color	MCB 4P 125A (main) and 2 RCBO 4P 63A 300mA	2			

N.B. Further combinations are possible on request. Other dimensions from the standard ones are subject to the type of set up.