

SERIES MODULUS M

Portable Distribution panels

Features

- Low linear density polyethylene enclosure, light and resistant to harsh use and shocks in compliance with Glow wire test 960°C according to EN60695-2-11: 2013, EN60695-2-10: 2013, CEI IEC60695-2-11: 2014, CEI IEC60695-2-10: 2014
- Transparent polycarbonate hinged lid with closing spring to protect the MCBs
- Available with CEE P17 receptacles IP44, IP67 black color and/or Socapex connectors
- Receptacles protected with MCB, RCD and/or RCBO
- LED indicator lights
- Integrated carriage handles
- Stackability
- Custom solutions available on demand
- Built in compliance with CEI EN 61439-1 / CEI EN 61439-2



Series Modulus	Supply	Protections	Receptacles CEE P17				Socapex
			63A	32A	32A	16A	
Article			3P+N+E 	3P+N+E 	2P+E 	2P+E 	
H4L6315P16N/SPX	CEE inlet 400V 63A 3P+N+E	MCB 4P 63A and 30 RCBO 1P+N 30 mA				12	3
H4L12515P32N	CEE inlet 400V 125A 3P+N+E	MCB4P 125A, 3 RCBO 4P 32A 30 mA and 12 RCBO 1P+N 16A 30 mA		3	12		
H4L12516PVN	CEE inlet400V 125A 3P+N+E	MCB 4P 125A, 1 RCBO 4P 63A 30 mA, 3 RCBO 4P 32A 30 mA, 3 RCBO 1P+N 32A 30 mA and 9 RCBO 1P+N 16A 30 mA	1	3	3	9	

N.B. Further combinations are possible on request. Other dimensions from the standard ones are subject to the type of set up.