

SERIES MODULUS L

Portable Distribution panels

Features

- Low linear density polyethylene enclosure, light and resistant to harsh use and shocks in compliance with Glow wire test 960°C according to EN60695-2-11: 2013, EN60695-2-10: 2013, CEI IEC60695-2-11: 2014, CEI IEC60695-2-10: 2014
- Transparent polycarbonate hinged lid with closing spring to protect the MCBs
- Available with CEE P17 receptacles IP44, IP67 black color and/or Socapex connectors
- Receptacles protected with MCB, RCD and/or RCBO
- LED indicator lights
- Integrated carriage handles
- Stackability
- Custom solutions available on demand
- Built in compliance with CEI EN 61439-1 / CEI EN 61439-2



Series Modulus	Supply	Protections	CEE P17 Receptacles				
			125A	63A	32A	32A	16A
Article			3P+N+T 	3P+N+T 	3P+N+T 	2P+T 	2P+T 
HFLR25012PN	Powerlock 400A	MCB 4P 250A (main), 3 RCBO 4P 63A 30mA, 3 RCBO 4P 32A 30mA, 6 RCBO 1P+N 16A 30mA,		3	3		6
HFLR2506PS63PN	Powerlock 400A with through wiring	MCB 4P 250A (main), 6 RCBO 4P 63A 30mA		6			
HFLR40014PPN	Powerlock 400A with through wiring	MCB 4P 400A (main), 2 RCBO 4P 125A 30mA, 3 RCBO 4P 63A 30mA, 3 RCBO 4P 32A 30mA, 6 RCBO 1P+N 16A 30mA	2	3	3		6

N.B. Further combinations are possible on request. Other dimensions from the standard ones are subject to the type of set up.